

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier used on the label: Product Name:

PCSI S-100 Finish Remover

Other means of identification:

Recommended use of the chemical and restrictions on use:

Chemical manufacturer address and telephone number:	
Manufacturer Name:	Perma-Chink Systems, Inc.
Address:	1605 Prosser Road Knoxville, TN 37914 USA
Website:	www.permachink.com
General Phone Number:	800-548-3554
General Fax Number:	865-523-9475
Customer Service Phone Number:	865-524-7343

Emergency phone number: Emergency Phone Number:

CHEMTREC 1-800-424-9300

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):		
Signal Word:	WARNING.	
GHS Class:	Eye Irritation. Category 2B. Skin Irritation. Category 3.	
Hazard Statements:	H320 - Serious eye damage/eye irritation. H316 - Skin corrosion/irritation.	
Precautionary Statements:	 P264 - Wash hands thoroughly after handling. P265 - Do not touch eyes. P302+P352 - IF ON SKIN: Wash with plenty of water. P332+P317 - If skin irritation occurs: Get emergency medical help. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P317 - If eye irritation persists: Get emergency medical help.P362+P364 - Take off contaminated clothing and wash it before reuse. P280 - Wear protective gloves/protective clothing/eye protection/face protection. 	

Hazards not otherwise classified that have been identified during the classification process:

Potential Health Effects:	
Eye:	May cause eye irritation.
Skin:	May cause skin irritation.
Inhalation:	Prolonged or excessive inhalation may cause respiratory tract irritation
Ingestion:	May be harmful if swallowed. May cause vomiting.
Chronic Health Effects:	Prolonged or repeated contact may cause skin irritation.
Signs/Symptoms:	Overexposure may cause headaches and dizziness.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	None generally recognized.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:			
Chemical Name	CA S#	Ingredient Percent	EC Num.
Non hazardous	No Data	40 - 45 by weight	
.Water	7732-18-5	50 - 55 by weight	231-791-2
Sodium Metasilicate	6834-92-0	2 - 5 by weight	229-912-9

SECTION 4: FIRST AID MEASURES

Description of necessary	measures:
Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
. Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

NFPA Flammability:

NFPA Reactivity:

Suitable Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
Special protective equipment and	precautions for fire-fighters:
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
NFPA Ratings:	
NFPA Health:	

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

1

0

Personal Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment as listed in Section 8.
Environmental precautions:	
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Methods and materials for contain	inment and cleaning up:
Methods for containment:	Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering, diking or other means. Provide ventilation.
Methods for cleanup:	Clean up spills immediately observing precautions in the protective equipment section. Place into a suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water to remove trace residue.

SECTION 7: HANDLING and STORAGE

Precautions for safe handling:		
Handling:	Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.	
Hygiene Practices:	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.	
Conditions for safe storage, including any incompatibilities:		
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.	

EXPOSURE GUIDELINES:

Appropriate engineering controls:

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Individual protection measures:	
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.
PPE Pictograms:	

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State:	Liquid.
Physical State Appearance:	Liquid.
Color:	Green.
Odor:	Citrus odor
Odor Threshold:	No Data
Boiling Point:	212°F
Melting Point:	Not applicable.
Density:	8.6 - 8.8 lb./gal
Specific Gravity:	1.04 - 1.06
Solubility:	Miscible in water.
Vapor Density:	No Data
Vapor Pressure:	20 mm Hg @ 68 °F
Percent Volatile:	85 - 95
Evaporation Rate:	No Data
Evaporation Point:	No Data
pH:	10 - 14
Molecular Formula:	Mixture
Viscosity:	1700 - 2300 cP
Coefficient of Water/Oil Distribution:	No Data
Flammability:	No Data
Flash Point:	No Data
Lower Flammable/Explosive Limit:	Not applicable.
Upper Flammable/Explosive Limit:	Not applicable.
VOC Content:	No Data

SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability:

Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization:	Not reported.	
Conditions To Avoid:		
Conditions to Avoid:	Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.	
Incompatible Materials:		
Incompatible Materials:	Oxidizing agents. Strong acids and alkalis.	
SECTION 11: TOXICOLOGICAL INFORMATION		
TOXICOLOGICAL INFORMATION:		

Water:

Ingestion:

Oral - Rat LD50 - Lethal dose, 50 percent kill: >90 mL/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Sodium Metasilicate :

Ingestion:

Oral - Rat LD50 - Lethal dose, 50 percent kill: 1153 mg/kg [Gastrointestinal - Ulceration or bleeding from stomach Gastrointestinal - Ulceration or bleeding from duodenum Gastrointestinal - Ulceration or bleeding from small intestine] Oral - Rat LD50 - Lethal dose, 50 percent kill: >1000 mg/kg [Gastrointestinal - Other changes] (RTECS)

SECTION 12: ECOLOGICAL INFORMATION

SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name:	Not restricted as a dangerous good.
DOT UN Number:	Not restricted as a dangerous good.
IATA Shipping Name:	Not restricted as a dangerous good.
IATA UN Number:	Not restricted as a dangerous good.
Canadian Shipping Name:	Not restricted as a dangerous good.
Canadian UN Number:	Not restricted as a dangerous good.
IMDG UN Number :	Not restricted as a dangerous good.
IMDG Shipping Name :	Not restricted as a dangerous good.
ADR UN Number:	Not restricted as a dangerous good.
ADR Shipping Name :	Not restricted as a dangerous good.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

<u>Water</u> :	
EC Number:	231-791-2
Sodium Metasilicate :	
TSCA Inventory Status:	Listed
Canada DSL:	Listed
EC Number:	229-912-9

HMIS Ratings:		Health Hazard	1
HMIS Health Hazard:	1	Fire Hazard	1
HMIS Fire Hazard:	1	Reactivity	0
HMIS Reactivity:	0	Personal Protection	×
HMIS Personal Protection:	X		
SDS Creation Date:	July 30, 2015		
SDS Revision Date:	July 27, 2022		
SDS Format:			
SDS Author:	Perma-Chink Systems, Inc.		
Disclaimer:	The information contained herein is, to the best of Perma-Chink S of the date indicated. Since the information contained herein may our control and with which we may be unfamiliar, and since data m date hereof may suggest modifications of the information, we do r results of its use. This information is furnished on the condition tha their own determination as to the suitability of the material for thei	be applied under conditions bey ade available subsequent to the not assume responsibility for the at the person receiving it shall r	yon e e