

SAFETY DATA SHEET

1. Product Identification

Product name Perma-Chink E-Wood Putty (PART B)

SDS Number 1600B00

Product type Polyamide Resin Mixture

Recommended use of the chemical and

restrictions on use

Recommend for, but not limited to, the restoration and repair of damaged

or rotted wood.

Restrictions None known.

Manufacturer/Supplier information

Company name Perma-Chink Systems, Inc.

Address 1605 Prosser Rd Ste 1

Knoxville, TN United States

Telephone (800) 548-3554

Website www.permachink.com
Email info@permachink.com

Emergency Contact CHEMTEL (U.S. and CANADA) 1-800-704-9215

CHEMTEL (Outside the U.S.) – Call Collect accepted +1-360-256-7365

2. Hazard(s) Identification

Classification of substance or

mixture/Signal Word

WARNING.

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2

Skin Sensitization – Category 1 Acute Aquatic Toxicity – Category 1 Chronic Aquatic Toxicity – Category 1

GHS Label Elements

Hazard Pictograms



Hazard Statements/Classification of

substance or mixture

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.H400 Very toxic to aquatic life.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

Precautionary Statements

Prevention

P202 Do not handle until all safety precautions have been read and

understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.P264 Wash hands and exposed skin thoroughly after handling.

P271 Use only outdoors or in a well ventilated area.

P272 Contaminated work clothes should not be allowed out of the workplace.

P273 Avoid release to the environment.

P279 Do not eat, drink or smoke when using this product.

P280 Wear eye protection/face protection. Wear protective gloves.

P285 In case of inadequate ventilation wear respiratory protection.

P314 Get medical advice/attention if you feel unwell. Response

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal P501 Dispose of contents/container to be specified in accordance with

regulations.

Hazards not otherwise classified (HNOC) None known.

3. Composition/Information On Ingredients

| Chemical Name | CAS Number | Content (%) |
|----------------------|-------------|-------------|
| Polyamide Polymer | Proprietary | 15 – 20% |
| Benzyl Alcohol | 100-51-6 | 15 – 20% |
| Nonyl Phenol | 84852-15-3 | 5 – 10% |
| Triethylenetetramine | 112-24-3 | <2% |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

4. First-Aid Measures

Eye contact

Storage

Skin contact Remove material from skin immediately by washing with soap and plenty of

water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Safety shower should be located in immediate work area.

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Get medical attention immediately. Suitable emergency

eye wash facility should be available in work area.

Ingestion Wash out mouth with water. Remove dentures if any. Remove victim to fresh

> air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or

are severe. Never give anything by mouth to an unconscious person. If

unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

waistband.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if

large quantities have been ingested or inhaled.

Specific treatments No specific treatment.

5. Fire-Fighting Measures

Suitable extinguishing mediaUse an extinguishing agent suitable for the surrounding fire.

Alcohol-resistant foam Carbon dioxide (CO₂)

Dry chemical, dry sand, limestone powder

Unsuitable extinguishing media Water (spray or stream).

Specific hazards arising from the chemical In a fire or if heated, a pressure increase will occur and the container may

burst. See also "Products of Combustion" in this section and Section 10. May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of

Hazardous decomposition productsMay generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the formation of very toxic aqueous solutions. Do not allow

run-off from firefighting to enter drains or watercourses. Incomplete combustion may form carbon monoxide. Ammonia gas may be liberated at high temperatures. In the case of incomplete combustion, an increased formation of oxides of nitrogen (NOx) is to be expected. Burning produces

noxious and toxic fumes.

Special protective actions for fire-fighters Promptly isolate the scene by removing all persons from the vicinity of the

incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done

without risk.

Special protective equipment for fire-

fighters

Fire fighters should wear appropriate protection equipment and self-contained

breathing apparatus (SCBA) with a full face-piece operated in a positive

pressure mode.

Further information None known.

6. Accidental Release Measures

Personal precautionsNo action shall be taken involving any personal risk or without suitable

training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal

protective equipment.

Emergency procedures If specialized clothing is required to deal with the spillage, take note of any

information in Section 8 on suitable and unsuitable materials. See also the

information in "For nonemergency personnel".

Methods and materials for containment/cleanup Small Spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert absorbent material and place in an appropriate waste disposal container.

Dispose of via a licensed waste disposal contractor. Wash the spill area clean

Large Spill

with water and detergent, observing environmental requirements. Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, watercourses, basements or confined areas. Contain and collect spillage with inert, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Wash the spill area clean with water and detergent, observing environmental requirements. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

7. Handling and Storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Avoid breathing vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Precautions/Recommendations for safe/proper storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits

| List | Components | CAS No. | Туре | Value |
|------|----------------------|----------|------|--------|
| OARS | Benzyl Alcohol | 100-51-6 | WEEL | 10 ppm |
| | Triethylenetetramine | 112-24-3 | WEEL | 1 ppm |

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures/Personal protective equipment

Eye/face protection Safety eyewear complying with an approved standard should be used when a

risk assessment indicates this is necessary to avoid exposure to liquid splashes,

mists, gases or dusts. Recommended: chemical safety goggles.

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Skin protection Personal protective equipment for the body should be selected based on the

task being performed and the risks involved and should be approved by a specialist before handling this product. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Respiratory protectionUse a properly fitted, air-purifying or air-fed respirator complying with an

approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards

of the product and the safe working limits of the selected respirator.

Special instructions for protection and

hygiene

Hand protection

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Discard contaminated leather goods. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical and Chemical Properties

Chemical family Polyamide curing agent

Appearance Epoxy putty

Physical State

Form Solid putty

Color Tan

Odor Mild ammonia odor

Density (Specific Gravity) 0.72 g/cm³

Viscosity 500,000 – 600,000 CPS @77°F

pH N/A

Melting point/freezing point N/A

Initial boiling point and boiling range N/A

Flash point N/A

Evaporation rate Slower than ether

Flammability (solid, gas)

Upper/lower flammability limit (by volume)

Upper flammability limit (by volume)

N/A

Lower flammability limit (by volume)

N/A

Material VOC

None

Vapor densityHeavier than airRelative densityNot determined

Solubility in water Negligible

Partition coefficient: n-octanol/water N/A

Auto-ignition temperature N/A

Decomposition temperature N/A

10. Stability and Reactivity

Reactivity Stable under normal conditions.

Chemical Stability Stable

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not

occur.

Conditions to avoid Epoxy resins and epoxy resin hardeners react with each other producing heat.

They should not be mixed with each other under uncontrolled conditions or in a large mass as the ensuing exothermic reaction may produce heat, smoke and

hazardous decomposition products.

Incompatible materials Organic and mineral acids.

Reaction with peroxides may result in violent decomposition of peroxide

possibly creating an explosion.

Reactive metals (e.g. sodium, calcium, zinc, etc).

Product slowly corrodes copper, aluminum, zinc and galvanized surfaces.

Materials reactive with hydroxyl compounds.

Oxidizing agents, amines, bases and reducing agents.

Nitrous acid and other nitrosating agents.

CAUTION! N-nitrosamines, many of which are known to be potent carcinogens, may be formed when the product comes in contact with nitrous acid, nitrites

or atmospheres with high nitrous oxide concentrations.

Hazardous decomposition productsOrganic acid vapors, nitric acid, ammonia, nitrogen and carbon oxides,

nitrosamine and aldehydes. Nitrogen oxide can react with water vapors to

form corrosive nitric acid.

Other hazards None known.

11. Toxicological Information

Acute Health Hazard (components)

No comprehensive data on product itself.

| Component | Result | Species | Dose | Exposure |
|----------------------|-------------|---------|---------------------|----------|
| Nonyl Phenol | LD50 Dermal | Rabbit | 2,031 mg/kg | - |
| | LD50 Oral | Rat | 1,412 mg/kg | - |
| Benzyl Alcohol | LD50 Oral | Rat | 1,620 mg/kg | - |
| Triethylenetetramine | LD50 Oral | Rat | 300 – 2,000 mg/kg | - |
| | LD50 Dermal | Rabbit | 1,000 – 2,000 mg/kg | - |

Irritation/Corrosion (components)

No information on the product itself.

| Component | Test | Result | Species |
|----------------|----------|-----------------|---------|
| Benzyl Alcohol | OECD 405 | Eyes - Irritant | Rabbit |

| Triethylenetetramine | Severe eye irritation | Rabbit |
|----------------------|------------------------|---------------|
| | Severe skin irritation | Rabbit – 24 h |

Sensitization

No information on the product itself.

No information on the product itself.

No information on the product itself.

| Component | CAS No | Test | Species | Result | Exposure |
|----------------------|----------|------|------------|------------------|----------|
| Triethylenetetramine | 112-24-3 | Skin | Guinea Pig | Causes burns | - |
| | | | | May cause | |
| | | | | sensitization by | |
| | | | | skin contact. | |

Mutagenicity No information on the product itself. Carcinogenicity No information on the product itself. **Reproductive Toxicity** No information on the product itself. Teratogenicity No information on the product itself.

Specific target organ toxicity (single

<u>exposure)</u>

Specific target organ toxicity (repeated

exposure)

Aspiration hazard No information on the product itself.

Potential acute health effects

Eye Contact Causes serious eye irritation. Inhalation May cause respiratory irritation.

Skin Contact Causes severe skin irritation. May cause a severe allergic reaction.

Ingestion Irritating to mouth, throat, and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eve Contact Causes serious eye irritation. Extended exposure may result in irreversible

damage to eye tissues. Adverse symptoms may include the following: Pain,

irritation, watering, redness or combination of noted symptoms.

Inhalation May cause respiratory irritation. Adverse symptoms may include the following:

> Respiratory tract irritation, coughing. Severe or extended exposure may induce central nervous system (CNS) effects: headache, nausea, dizziness, confusion,

breathing difficulties.

Skin Contact Causes skin irritation. May cause an allergic skin reaction. This material may be

> a strong skin sensitizer in certain susceptible persons. Once sensitized, most persons are unable to work around amine cured epoxy resins without an allergic reaction. Sensitized persons are not known to have other health problems as a result of sensitization. Adverse symptoms may include the following: Irritation and/or redness. Severe or extended exposure may result in absorption through skin which may induce central nervous system (CNS)

effects: headache, nausea, dizziness, confusion, breathing difficulties.

Ingestion Irritating to mouth, throat, and stomach. Adverse symptoms may include the

No information on the product itself.

following: Irritation/damage of mucous membranes. May cause central nervous system (CNS) effects: headache, nausea, dizziness, confusion,

breathing difficulties.

Delayed and immediate effects and also chronic effects from short and long term exposure

Potential chronic health effects

General Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

CarcinogenicityNo significant effects or critical hazards.MutagenicityNo significant effects or critical hazards.TeratogenicityNo significant effects or critical hazards.Developmental effectsNo significant effects or critical hazards.Fertility effectsNo significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates (ATEmix)

| Route | ATE value |
|---------------------|----------------|
| Oral | 4539.5 mg/kg |
| Dermal | 10,692.3 mg/kg |
| Inhalation (vapors) | 45.58 mg/l |

12. Ecological Information

Ecotoxicity

No information on the product itself.

| Component | Test | Species | Result | Exposure |
|----------------------|------|----------------|--------------------|----------|
| Nonyl Phenol | LC50 | Fathead minnow | 0.128 mg/l | 96 h |
| | EC50 | Water Flea | 0.0848 – 0.19 mg/l | 48 h |
| Benzyl Alcohol | LC50 | Fathead minnow | 460 mg/l | 96 h |
| Triethylenetetramine | LC50 | Fathead minnow | >100 mg/l | 96 h |

Persistence and degradability

No information on the product itself.

| Component | Test | Period | Result |
|----------------|--|---------|--------|
| Nonyl Phenol | EPA OPPTS | 63 days | 100% |
| | OECD | 56 days | 50% |
| | OECD 301B Ready Biodegradability – CO2 | 35 days | 48.2% |
| | Evolution Test | | |
| Benzyl Alcohol | Readily biodegradable | | |

Bioaccumulative Potential

No information on the product itself.

| Component | LogPow | BCF | Potential |
|----------------|--------|-------------------|-----------|
| Nonyl Phenol | 5.4 | 740 | High |
| Benzyl Alcohol | 1.05 | 1.37 (calculated) | Low |

Mobility in Soil No information on the product itself.

Soil/water partition coefficient (KOC) Data not available.

Other adverse effects No known significant effects or critical hazards.

13. Disposal Considerations

Waste from residues/ unused products

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of

surplus and non-recyclable products via a licensed waste disposal contractor.

Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Contaminated packaging

Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International Transport Regulations

| Regulatory information | UN/NA number | Proper Shipping Name | Classes/*PG | Additional Information |
|------------------------|--------------|--|-------------|------------------------|
| DOT | | Non-regulated | | |
| TDG | | Non-regulated | | |
| IMO/IMDG | UN3082 | Environmentally hazardous substance, liquid, n.o.s. (Nonyl Phenol) | Class 9 III | Marine pollutant |
| IATA | UN3082 | Environmentally hazardous substance, liquid, n.o.s. (Nonyl Phenol) | Class 9 III | |
| *PG: Packing group | | | | |

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to

do in the event of an accident or spillage.

15. Regulatory Information

Special precautions for user:

UNITED STATES

| U.S. Federal Regulations | United States – TSCA 12(b) – Chemical export notification: None Required. |
|--------------------------|--|
| | United States – TSCA 5(a)2 – Final significant new use rules: Not Listed. |
| | United States – TSCA 5(a)2 – Proposed significant new use rules: Not Listed. |
| | United States – TSCA 5(e) – Substance consent order: Not listed. |

Clean Air Act – Ozone Depleting Substances (ODS)

Clean Air Act Section 113/h) Hazardou

This product does not contain nor is it manufactured with ozone depleting substances.

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

Pher

Product Name Concentration %
Phenol 0 - 1

Pennsylvania – RTK Phenol

California Prop. 65 None required.

EPA SARA 302 Extremely Hazardous

Substances

None.

EPA SARA 302/304/311/312 Hazardous

Chemicals SARA 313

Acute Health Hazard

| Product Name | Concentration % |
|--------------|-----------------|
| | |

Form R - Reporting requirements

CERCLA Hazardous substances

| Phenol | | 0 - 1 | | |
|-----------|---|---|---|--|
| Component | % | Section 304 CERCLA Hazardous Substance | CERCLA Reportable Quantity (Lbs) | Product Reportable Quantity (Lbs) |
| Phenol | 1 | Listed | | |

United States inventory (TSCA 8b)

All components are listed or exempted.

CANADA

WHMIS (Canada) Class D-2B: Material causing other toxic effects (Toxic).

Canadian NPRINone required.CEPA Toxic substancesNone required.

INTERNATIONAL REGULATIONS

International Lists Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted. **Korea inventory:** All components are listed or exempted. **Japan inventory:** All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

New Zealand inventory (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

Taiwan inventory (CSNN): All components are listed or exempted.

16. Other Information, Including Date of Preparation or Last Revision

HMIS Rating



Date of Preparation October 27, 2023

Date of Last Revision March 2, 2023

Revision # 7.0

More Information (800) 548-3554

The information contained herein is based on the data available to us and is believed to be correct. However, Perma-Chink Systems, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Perma-Chink Systems, Inc. assumes no responsibility for injury from the use of the product described herein.